*

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version number 9

Revision: 10.09.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- Trade name: Milacor Whiteboard Finish Low VOC Hardener Komponente B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Application of the substance / the mixture Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier: Milacor GmbH Grüner Weg 10
33449 Langenberg
T: +49 5248 821434
F +49 5248 6837
info@milacor.de
www.milacor.de

· 1.4 Emergency telephone number: +49 5248 821434

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

GHS07

| Acute Tox. 4 | H332 Harmful if inhaled. |
|--------------|---|
| Skin Sens. 1 | H317 May cause an allergic skin reaction. |
| STOT SE 3 | H335 May cause respiratory irritation. |
| | |

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

- Hazard-determining components of labelling: Hexamethylene diisocyanate, oligomers Polyoxyethylene tridecyl ether phosphate 2-butoxyethyl acetate cyclohexyldimethylamine Hazard statements H222 Harmful if inbalad
- H332 Harmful if inhaled. H318 Causes serious eye damage. H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.

(Contd. on page 2)

Printing date 10.09.2018

Safety data sheet according to 1907/2006/EC, Article 31

according to 1907/2006/EC, Article 31 Version number 9

Revision: 10.09.2018

Trade name: Milacor Whiteboard Finish Low VOC Hardener Komponente B

(Contd. of page 1)

| H412 Harmful | to aquatic life with long lasting effects. |
|-------------------|--|
| · Precautionary | statements |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P280 | Wear protective gloves / eye protection / face protection. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P305+P351+P | 338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if |
| | present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTER/doctor. |
| P405 | Store locked up. |
| · Additional info | rmation: |
| EUH204 Conta | ins isocyanates. May produce an allergic reaction. |
| Restricted to pr | ofessional users. |
| · 2.3 Other haza | rds |
| · Results of PBT | and vPvB assessment |
| · PBT: Not appli | icable. |

PBT: Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|--|--|-----------------------------|
| CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17 01-2119488934-20 | | 50-100% |
| CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47 | 2-butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 | 2.5-<10% |
| CAS: 9046-01-9 | Polyoxyethylene tridecyl ether phosphate Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315 | 2.5-<10% |
| CAS: 98-94-2 EINECS: 202-715-5 Reg.nr.: 01-2119533030-60 | cyclohexyldimethylamine ♦ Flam. Liq. 3, H226; ♦ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ♦ Skin Corr. 1B, H314; ♦ Aquatic Chronic 2, H411 | ≥ 0.25-<1% |
| CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37 | hexamethylene-di-isocyanate Acute Tox. 2, H330; & Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 | <i>≥</i> 0.1- <i>≤</i> 0.5% |
| • Additional information: For | STOT SE 3, H335 r the wording of the listed hazard phrases refer to section 16 | |

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

⁻ GB

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version number 9

Revision: 10.09.2018

Trade name: Milacor Whiteboard Finish Low VOC Hardener Komponente B

(Contd. of page 2)

• After eye contact:

- *Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.* • *After swallowing:* If symptoms persist consult doctor.
- 4.3 Indication of any immediate medical attention and special treatment needed
- *No further relevant information available.*
- · Information for doctor:

SECTION 5: Firefighting measures

*

- 5.1 Extinguishing media
- \cdot Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture In case of fire, the following can be released: Nitrogen oxides (NOx)
- Carbon monoxide (CO)
- Hydrogen cyanide (HCN)
- 5.3 Advice for firefighters
- \cdot **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Contain and collect spillages with non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth) and place in a suitable container.

Decontaminate immediately with suitable mixture (flammable):

- as such usable (inflammatory!):

| water | 45 Vol.% |
|---------------------------------------|----------|
| ethanol or isopropanol | 50 Vol.% |
| ammonia solution ($Density = 0.88$) | 5 Vol.% |
| - alternatively (non-flammable): | |
| sodium carbonate | 5 Vol.% |
| water | 95 Vol.% |
| | |

Add the same decontaminant to any residues and allow to stand for several days in an non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of in accordance with the waste regulations (see Section 13).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

GB

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version number 9

Revision: 10.09.2018

Trade name: Milacor Whiteboard Finish Low VOC Hardener Komponente B

(Contd. of page 3)

Prevent formation of aerosols.

Persons with a history of asthma, allergies or chronic or recurrent respiratory diseases should only be employed in processes in which this product is used under appropriate medical supervision. • Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis. Store away from foodstuffs.

• Further information about storage conditions: Keep container tightly sealed. Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohol and water.

• Storage class: 10

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

28182-81-2 Hexamethylene diisocyanate, oligomers

EBW Short-term value: 0.5 mg/m³ exposition evaluation valu TRGS 430 (EBW)

112-07-2 2-butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk

822-06-0 hexamethylene-di-isocyanate

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen; as -NCO

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

Short term filter device:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version number 9

Revision: 10.09.2018

Trade name: Milacor Whiteboard Finish Low VOC Hardener Komponente B

(Contd. of page 4)

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

*

Butyl rubber, BR

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

| 9.1 Information on basic physical an | d chemical properties | |
|---------------------------------------|---|--|
| General Information | * * | |
| Appearance: | | |
| Form: | Fluid | |
| Colour: | According to product specification | |
| Odour: | Characteristic | |
| Odour threshold: | Not determined. | |
| pH-value: | Not determined. | |
| Change in condition | | |
| Melting point/freezing point: | Undetermined. | |
| Initial boiling point and boiling rai | nge: 184-195°C | |
| Flash point: | 78°C (DIN 53213) | |
| Flammability (solid, gas): | Not applicable. | |
| Ignition temperature: | 280°C (DIN 51794) | |
| Decomposition temperature: | Not determined. | |
| Auto-ignition temperature: | Product is not selfigniting. | |
| Explosive properties: | Product does not present an explosion hazard. | |
| Explosion limits: | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| Vapour pressure at 20°C: | 0.4 hPa | |
| Density at 20°C: | 1.127 g/cm ³ (DIN 53217) | |
| Relative density | Not determined. | |
| Vapour density | Not determined. | |

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version number 9

Revision: 10.09.2018

Trade name: Milacor Whiteboard Finish Low VOC Hardener Komponente B

| | | (Contd. of page 5 |
|---|--|-------------------|
| · Evaporation rate | Not determined. | |
| · Solubility in / Miscibility with water: | Fully miscible. | |
| · Partition coefficient: n-octanol/water: | Not determined. | |
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic at 20°C: | 210 s (DIN 53211/4) | |
| · Solvent content: | | |
| VOC (EC) | 9.09 % | |
| Solids content (weight-%): | 90.9 % | |
| • 9.2 Other information | No further relevant information available. | |

SECTION 10: Stability and *reactivity*

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Possible in traces. Nitrogen oxides Hydrogen chloride (HCl) Hydrogen cyanide (prussic acid) Carbon monoxide Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity
- Harmful if inhaled.
- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- \cdot Serious eye damage/irritation
- Causes serious eye damage.
- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- \cdot Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure
- May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version number 9

Revision: 10.09.2018

Trade name: Milacor Whiteboard Finish Low VOC Hardener Komponente B

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Harmful to aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

| · 14.1 UN-Number · ADR, ADN, IMDG, IATA | Void | |
|--|-----------------|-------------------|
| · 14.2 UN proper shipping name | | |
| · ADR, ADN, IMDG, IATA | Void | |
| · 14.3 Transport hazard class(es) | | |
| · ADR, ADN, IMDG, IATA | | |
| · Class | Void | |
| · 14.4 Packing group | | |
| · ADR, IMDG, IATA | Void | |
| · 14.5 Environmental hazards: | | |
| · Marine pollutant: | No | |
| · 14.6 Special precautions for user | Not applicable. | |
| · 14.7 Transport in bulk according to Ann | ex II of | |
| Marpol and the IBC Code | Not applicable. | |
| | | (Contd. on page 8 |

according to 1907/2006/EC, Article 31

Printing date 10.09.2018

Version number 9

Revision: 10.09.2018

(Contd. of page 7)

Trade name: Milacor Whiteboard Finish Low VOC Hardener Komponente B

· UN "Model Regulation":


Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:



· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour. H301 Toxic if swallowed. H302 Harmful if swallowed. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H330 Fatal if inhaled. H331 Toxic if inhaled. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H411 Toxic to aquatic life with long lasting effects. · Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 3: Acute toxicity - Category 3 (Contd. on page 9) GB

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 10.09.2018

Printing date 10.09.2018

Version number 9

Trade name: Milacor Whiteboard Finish Low VOC Hardener Komponente B

(Contd. of page 8)

GB

Acute Tox. 2: Acute toxicity - Category 2 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 \cdot * Data compared to the previous version altered.